

# EPIC EDI101

**CEE: Bridges Interfaces Application Essentials Exam (2026  
Version)**

**For More Information – Visit link below:**

**<https://www.examsempire.com/>**

**Product Version**

- 1. Up to Date products, reliable and verified.**
- 2. Questions and Answers in PDF Format.**



**<https://examsempire.com/>**

**Visit us at: <https://www.examsempire.com/edi101>**

# Latest Version: 6.0

## Question: 1

Which of the following refers to specifically the 2nd component in the 5th field of PID?

- A. PID-5[2]
- B. PID-5.2
- C. PID52
- D. PID-5^2

**Answer: B**

Explanation:

In HL7 v2 messaging, a standard naming convention is used to identify specific data locations. The format follows Segment-Field.Component.Subcomponent. For example, PID-5 represents the Patient Name field. To specify a component within that field (like the Given Name, which is the 2nd component), a dot is used as a separator. Therefore, PID-5.2 correctly identifies the 2nd component of the 5th field.

## Question: 2

What segments are defined as custom in HL7 version 2?

- A. Z-segment
- B. NTE
- C. X-segment
- D. PID

**Answer: A**

Explanation:

HL7 provides a standard set of segments (like PID for Patient Identity or MSH for Message Header). However, to allow for site-specific data that doesn't fit into standard segments, HL7 reserves the letter "Z" for custom segments. Any segment starting with "Z" (e.g., ZPV, ZCD) is considered a local, non-standard extension defined by the specific healthcare organization or vendor.

### Question: 3

Assuming that your message starts with MSH|, which of the following strings would you need to escape a portion of? (SELECT ALL THAT APPLY)

- A. patient & their mother arrived at the ED
- B. copay: \$10.00
- C. this procedure will be performed @ EMC family Medicine
- D. they took ~10mg of this medication

**Answer: A, D**

Explanation:

HL7 uses specific characters as delimiters to separate data. Based on a standard MSH segment (MSH|^~&), the characters & (subcomponent separator) and ~ (repetition separator) are special characters. If these characters appear as part of the actual data text, they must be "escaped" using the escape character (usually \) so the interface parser doesn't mistake them for structural separators.

### Question: 4

Which of the following can be parts of an XML message? (SELECT ALL THAT APPLY)

- A. Attribute
- B. Processing ID
- C. Subcomponent Separator
- D. Namespace
- E. Element

**Answer: A, D, E**

Explanation:

XML messages are structured differently than HL7. Core components of XML include Elements (the tags that contain data), Attributes (properties provided within an element tag), and Namespaces (used to provide uniquely named elements and attributes in an XML document). "Subcomponent Separator" and "Processing ID" are specific to HL7 and are not native structural components of XML.

### Question: 5

Which queue is unique to outgoing interfaces?

- A. Holding Queue
- B. Data Queue
- C. Event Queue
- D. Control Queue

**Answer: C**

Explanation:

The Event Queue is the first stop for outgoing data. When an action occurs in Epic (like a discharge), a trigger is placed in the Event Queue. The Event Daemon then picks up this trigger to build the actual message. Incoming interfaces do not use an Event Queue because the message is already built by the external system when it arrives.

**Thank You for Trying Our Product**  
**Special 16 USD Discount Coupon: NSZUBG3X**

**Email:** [support@examsempire.com](mailto:support@examsempire.com)

**Check our Customer Testimonials and ratings  
available on every product page.**

**Visit our website.**

**<https://examsempire.com/>**