

Dell EMC D-PDD-DY-01

Dell Technologies PowerProtect Data Domain Deploy V2

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/d-pdd-dy-01>

Latest Version: 6.0

Question: 1

What is the maximum number of concurrently active virtual tape library instances on each PowerProtect DD appliance?

- A. 32
- B. 56
- C. 64
- D. 128

Answer: C

Question: 2

Which types of replication are supported in a PowerProtect DD appliance?

- A. Collection, Directory, MTree, Pool, and Managed File
- B. MTree, Collection, and Directory only
- C. Synchronous, Collection, MTree, Managed File, and Directory
- D. Asynchronous, Collection, Directory, and MTree

Answer: B

Question: 3

An engineer is attempting to add an ES40 shelf to a PowerProtect DD9400. The system currently has one DS60 and four ES40 shelves on the same chain. The system does not recognize the additional shelf. Why has this occurred?

- A. The maximum number of shelves on the chain is exceeded
- B. An active tier license must be added for additional storage
- C. ES40 and DS60 shelves must be placed on separate chains
- D. The system capacity license is insufficient

Answer: A

Question: 4

In a backup environment with PowerProtect DD VTL, which process is no longer needed?

- A. Manage tape library
- B. Shipping the tapes
- C. FC SAN Zoning
- D. Manage Backup catalog

Answer: B

Question: 5

How many hot spare drives does the DS60 have?

- A. 2, 4, 6, or 8
- B. 3, 6, 9, or 12
- C. The system uses distributed sparring instead of hot spares
- D. 1, 2, 3, or 4

Answer: D

Question: 6

Which backup applications create their own storage units when they are configured to use a PowerProtect DD appliance as a backup target?

- A. Dell EMC Avamar and Veritas Backup Exec
- B. Dell EMC NetWorker and Avamar
- C. Veritas Backup Exec and NetBackup
- D. Veritas NetBackup and Dell EMC NetWorker

Answer: B

Question: 7

An engineer is deploying a PowerProtect DD6900 system. The installation includes ES40, and DS60 expansion shelves on the same chain. What consideration should be made when configuring the hardware?

- A. The maximum number of ES40 shelves is four
- B. The maximum number of DS60 shelves is five
- C. The maximum number of ES40 shelves is six

D. The maximum number of DS60 shelves is six

Answer: A

Question: 8

What is the maximum number of supported tape drives that can be configured using PowerProtect DD with at least 60 CPU cores?

- A. 526
- B. 512
- C. 1080
- D. Unlimited

Answer: C

Question: 9

During a normal workday an administrator notices poor performance (<1MB/s) in combination with poor global compression rate (<1x). What metrics should be monitored to find the issue?

- A. Cleaning, NVRAM battery level, and link utilization
- B. Stream count, CPU utilization, and replication
- C. Stream count, disk reconstruction, and replication
- D. NVRAM battery level, link utilization, and disk reconstruction

Answer: B

Question: 10

An administrator notices that several disks on a shelf show as unknown. What should be done to resolve this issue?

- A. Enter the disk unfail command for the unknown disks
- B. Ensure the expansion shelf is cabled properly
- C. Cycle the power on the newly added expansion shelf
- D. Enter the storage add enclosure command

Answer: A

Thank You for Trying Our Product
Special 16 USD Discount Coupon: NSZUBG3X
Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>