

HP HPE4-A52

Aruba Certified Campus Access Switching Expert Practical Exam

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/hpe4-a52>

Latest Version: 6.0

Question: 1

You are tasked to configure a VSX pair between two Aruba CX switches. Configure both switches with multi-chassis LAG on interface 1/1/1 and use VLAN 10 for the ISL.

A. See the Explanation.

Answer: A

Explanation:

1. On both switches, enter VSX mode:

vsx

inter-switch-link lag 100

peer-link lag 100

keepalive vlan 10 source 1.1.1.1 destination 1.1.1.2

2. Create LAG 100:

interface lag 100

no shutdown

vlan trunk native 1

vlan trunk allowed all

3. Add interface 1/1/1 to LAG:

interface 1/1/1

lag 100

4. Enable VSX: vsx enable

Question: 2

Configure VSF on two Aruba 2930F switches connected via ports 1/1/49 and 1/1/50.

A. See the Explanation.

Answer: A

Explanation:

1. On switch 1:

vsf member 1 link 1 1/1/49

vsf member 1 link 2 1/1/50

vsf enable domain 10

write memory

reload

2. On switch 2:

vsf member 2 link 1 1/1/49

```
vsf member 2 link 2 1/1/50
vsf enable domain 10
write memory
reload
```

Question: 3

Verify and troubleshoot a VSX synchronization issue between two CX switches.

A. See the Explanation.

Answer: A

Explanation:

1. Run the command: show vsx status
2. Confirm ISL and Keepalive are both UP.
3. If Sync status is Not Synchronized:
 - o Check VLAN configuration consistency.
 - o Check the LAG interface configuration using:
show interface lag 100
4. Run:
show vsx config-consistency
and correct any mismatches.

Question: 4

Implement Distributed LAG (MC-LAG) between a server and two Aruba CX switches in VSX.

A. See the Explanation.

Answer: A

Explanation:

1. On each VSX switch, configure:
interface lag 200 multi-chassis
vlan trunk native 1
vlan trunk allowed all
2. Add uplink interface to LAG:
interface 1/1/2
lag 200
no shutdown
3. On the server side, configure LACP with both links into same bond.
4. Verify LAG:
show lacp interface

Question: 5

Configure VSX using best practices with separate management VRF.

A. See the Explanation.

Answer: A

Explanation:

1. Create management VRF: vrf attach mgmt
2. Set up keepalive using VRF:
vsx
keepalive vrf mgmt source 10.0.0.1 destination 10.0.0.2
3. Verify via: show vsx status
4. Ensure dedicated physical path (not ISL) for keepalive traffic.

Thank You for Trying Our Product

Special 16 USD Discount Coupon: NSZUBG3X

Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>