

# Cisco 300-920

## Developing Applications for Cisco Webex and Webex Devices (DEVWBX)

For More Information – Visit link below:

<https://www.examsempire.com/>

**Product Version**

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/300-920>

## Question: 1

DRAG DROP

Drag and drop the components to create the authentication header used for the Webex Teams API.

Not all options are used.

<input type="text"/>	:	<input type="text"/>	<input type="text"/>
----------------------	---	----------------------	----------------------

admin:Password12345!	Authorization
Token	Bearer
BH782kjh-2jkhmnb3rlkj3lkjnm3klj3	Authentication
Basic	

**Answer:**

Authorization	:	Bearer	Token
---------------	---	--------	-------

Reference:

<https://developer.webex.com/docs/guest-issuer>

## Question: 2

Refer to the exhibit.

```

const xml = '<?xml version= "1.0" encoding= "UTF-8"?>
<serv:message xmlns:xsi= "http://www.w3.org/2001/XMLSchema-instance"
xmlns:serv="http://www.webex.com/schemas/2002/06/service"
xsi:schemaLocation="http://www.webex.com/schemas/2002/06/service"
http://www.webex.com/schemas/2002/06/service/service.xsd">
  <header>
    <securityContext>
      <webExID>admin@cisco.com</webExID>
      <password>password</password>
      <siteName>cisco</siteName>
      <returnAdditionalInfo>true</returnAdditionalInfo>
    </securityContext>
  </header>
  <body>
    <bodyContent xsi:type= "java:com.webex.service.binding.user.SetUser">
      <webExId>user@cisco.com</webExId>
      <personalMeetingRoom>
        <hostPIN>3421</hostPIN>
      </personalMeetingRoom>
    </bodyContent>
  </body>
</serv:message>;
var xmlhttp = new XMLHttpRequest();

<< missing code >>

xmlhttp.setRequestHeader('Content-Type', 'text/xml');
xmlhttp.send(xml);

```

A developer must construct an HTTP Request to use the XML API to set a Personal Meeting Room PIN for a given user.

Which code completes the code to create the request?

- A. xmlhttp.open("GET", "https://cisco.webex.com/WBXService/XMLService");
- B. xmlhttp.open("PATCH", "https://cisco.webex.com/WBXService/XMLService");
- C. xmlhttp.open("PUT", "https://cisco.webex.com/WBXService/XMLService");
- D. xmlhttp.open("POST", "https://cisco.webex.com/WBXService/XMLService");

**Answer: D**

Explanation:

The post method can be used for HTTP request that sets up a personal meeting room PIN for a user.

### Question: 3

Which expression is a valid Webex Teams webhook filter?

- A. personEmail=person@example.com+roomId=abc123
- B. personEmail=person@example.com-roomId=abc123
- C. personEmail=person@example.com&roomId=abc123
- D. personEmail=person@example.com,roomId=abc123

**Answer: C**

Explanation:

You can also use more than one filter in a webhook. To use multiple filters, combine them with the “&” symbol. For example, to create a webhook that only sends notifications when a specific person performs an action in a specific room, such as sending a message or creating a membership, combine the personEmail and roomId filters.

Reference:

<https://developer.webex.com/docs/api/guides/webhooks>

### Question: 4

Which REST API request is used to list all the Webex Room Kit devices within a large organization so that a new custom In-Room Control can be deployed on all the devices?

A.

```
var request = require("request");
var options = { method: 'GET',
  url: 'https://api.ciscospark.com/v1/devices',
  qs: { product: 'Roomkit' },
  headers:
    { 'Content Type': 'application/json',
      Authorization: 'Bearer Yz6FgoWx7Pgb57C9z' }};

request(options, function(error, reponse, body) {
  if (error) throw new Error(error);
  console.log(body);
});
```

B.

```
var request = require("request");
var options = { method: 'GET',
  url: 'https://api.ciscospark.com/v1/devices',
  qs: { product: 'Roomkit' , placeID: 'Yzb60gRx3kBq5iB2w' },
  headers:
    { 'Content Type': 'application/json',
      Authorization: 'Bearer Yz6FgoWx7Pgb57C9z' }};

request(options, function(error, reponse, body) {
  if (error) throw new Error(error);
  console.log(body);
});
```

C.

```
var request = require("request");
var options = { method: 'GET',
  url: 'https://api.ciscospark.com/v1/devices/Yzb60gRx3kBq5iB2w',
  qs: { deviceName: 'Roomkit' },
  headers:
    { 'Content Type': 'application/json',
      Authorization: 'Bearer Yz6FgoWx7Pgb57C9z' } };

request(options, function(error, reponse, body) {
  if (error) throw new Error(error);
  console.log(body);
});
```

D.

```
var request = require("request");
var options = { method: 'GET',
  url: 'https://api.ciscospark.com/v1/devices',
  qs: { upgradeChannel: 'Roomkit' },
  headers:
    { 'Content Type': 'application/json',
      Authorization: 'Bearer Yz6FgoWx7Pgb57C9z' } };

request(options, function(error, reponse, body) {
  if (error) throw new Error(error);
  console.log(body);
});
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: A**

Explanation:

The qs: option is required to list all roomkit devices. Product: 'RoomKit' is the correct option because it will list all roomkit devices.

## Question: 5

DRAG DROP

Drag and drop the code onto the snippet to construct the JavaScript to create a new meeting with the

Webex Meetings XML API. Options can be used more than once.

```
var http = require('https');
var xml = '<?xml version="1.0" encoding="UTF-8"?>
  <serv:message xmlns:serv="http://www.webex.com/schemas/2002/06/service"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <header><securityContext>
      <siteName>mySite</siteName>
      <webExID>Ciscouser</webExID>
      <[redacted]>
PD4WiqNfrKxBR19B...RERJTkdfU0hBMjU2X0FMR09SSVRITV8=
</[redacted]>
    </securityContext></header>
    <body>
      <bodyContent xsi:type="java.com.webex.service.binding.meeting.CreateMeeting">
        <metaData><confName>Sample Meeting</confName>
        <meetingType>105</meetingType></metaData>
        <schedule><startDate>12/13/2019 11:59:5</startDate></schedule>
      </bodyContent>
    </body>
  </serv:message>
var req = http.request('https://api.webex.com/WBXService/XMLService',
  [redacted] );
req.write(xml);
req.end();
```

{ 'method' : 'POST' }

{ 'method' : 'PUT' }

accessToken

sessionTicket

**Answer:**

```

var http = require('https');
var xml = '<?xml version= "1.0" encoding= "UTF-8"?>
    <serv:message xmlns:serv= "http://www.webex.com/schemas/2002/06/service"
        xmlns:xsi= "http://www.w3.org/2001/XMLSchema-instance">
        <header><securityContext>
            <siteName>mySite</siteName>
            <webExID>Ciscouser</webExID>
            < { 'method' : 'POST' } >
PD4WiqNfRkxBR19B...RERJTkdfU0hBMjU2X0FMR09SSVRITV8=
        </
            accessToken
        >
            </securityContext></header>
            <body>
            <bodyContent xsi:type= "java.com.webex.service.binding.meeting.CreateMeeting">
                <metaData><confName>Sample Meeting</confName>
                <meetingType>105</meetingType></metaData>
                <schedule><startDate>12/13/2019 11:59:5</startDate></schedule>
            </bodyContent>
            </body>
            </serv:message>
var req = http.request('https://api.webex.com/WBXService/XMLService',
    sessionTicket
);
req.write(xml);
req.end();

```



**Thank You for Trying Our Product**

**Special 16 USD Discount Coupon: NSZUBG3X**

**Email:** [support@examsempire.com](mailto:support@examsempire.com)

**Check our Customer Testimonials and ratings  
available on every product page.**

**Visit our website.**

**<https://examsempire.com/>**