

Latest Version: 6.0

Question: 1

Identify the activities involved in SAP OS/DB Migration Check Verification?
There are 2 correct answers to this question

- A. Analyze the SAP System and database system logs
- B. Analyze the response of multiple component
- C. Analyze the performance in the DB system
- D. Analyze the response times of the critical transactions

Answer: A, D

Question: 2

What are the Typical warning in R3SZCHK.log if reaching the size limit?
There are 2 correct answers to this question

- A. WARNING: REPOLOAD in SLEXC: initial extent reduced to 1782579201
- B. WARNING: /BLUESKY/FECOND in APPLO: initial extent reduced to 1782579222
- C. WARNING: REPOLOAD in SLEXC: initial extent reduced to 1782579200
- D. WARNING: /BLUESKY/FECOND in APPLO: initial extent reduced to 1782579200

Answer: C, D

Question: 3

Which source does R3LOAD use to populate the TSK files?
Please choose the correct answer.

- A. Structure files
- B. ABAP data dictionary
- C. Database data dictionary
- D. Extent files

Answer: A

Question: 4

How does R3LOAD handle restart situations based on the task file content?

There are 2 correct answers to this question

- A. If a status is „err" for a create index task, R3LOAD will drop the index and recreate it to restart the import.
- B. If the status is „err" for a data import task, R3LOAD will drop the table to restart the import.
- C. If the status is „err" for a create primary key task, R3LOAD will delete data and recreate the primary key to restart the import.
- D. If the status is „err" for a create table task, R3LOAD will drop and recreate the table to restart the import.

Answer: C, D

Question: 5

Which SAP Migration Tool writes its data in a format that is independent of database and platform?

Please choose the correct answer.

- A. JLOAD
- B. JSLOAD
- C. JSAPINST
- D. JPKCT

Answer: A