

Latest Version: 6.0

Question: 1

The drive test scenario judges the success of the handover, usually based on the signaling. On the terminal side, which of the following signaling starts the handover process?

- A. Measurement Control
- B. Measurement Report
- C. Handover Request
- D. Handover Command

Answer: B

Question: 2

In the process of LTE network optimization, which of the following data sources are used for problem location analysis? (multiple choice)

- A. Project Files
- B. Traffic statistics and alarm data
- C. useUser complaint record
- D. Signaling data
- E. netNetwork test data

Answer: BCDE

Question: 3

Before coverage analysis, it is necessary to obtain basic data such as the planning plan, site distribution, base station configuration, antenna feeder configuration, RS power and service load characteristics of the optimized target area. Then obtain the information of the existing network data, conduct a comparative analysis, and find out the areas where the coverage problem may exist.

- A. True
- B. False

Answer: A

Question: 4

Regarding TA planning, which of the following statements is incorrect?

- A. LTE of TA planning should be consistent with 2G/3G of LA plan to be consistent
- B. Currently LTE of TA can contain at most 16 pieces of TA
- C. LTE of TA number of cells in should be better than the corresponding 2G/3G LA small number of medium cells
- D. Each A single-operator cell can belong to multiple TA

Answer: D

Question: 5

Which of the following carrier bandwidths does LTE support? (multiple choice)

- A. 40M
- B. 5M
- C. 15M
- D. 20M

Answer: BCD