

Huawei

H12-725_V4.0

HCIP-Security (Written) V4.0

For More Information – Visit link below:

<https://www.examsempire.com/>

Product Version

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/h12-725-v4-0>

Latest Version: 6.0

Question: 1

Which of the following are common use cases for IPsec VPN?
(Choose two)

- A. Secure connection to cloud resources
- B. Bypassing firewall policies
- C. Encrypted site-to-site communication
- D. Public FTP access

Answer: A,C

Question: 2

During which emergency response phase is evidence collection and log preservation typically performed?

- A. Preparation
- B. Detection and Analysis
- C. Containment
- D. Post-Incident Recovery

Answer: B

Question: 3

Which Huawei firewall features enhance IPsec VPN reliability?
(Choose two)

- A. DPD (Dead Peer Detection)
- B. Uplink Load Balancing
- C. Certificate Pinning
- D. IPsec Policy Failover

Answer: A,D

Question: 4

What is the main goal of the emergency response process in cybersecurity?

- A. To improve NAT performance
- B. To ensure high bandwidth usage
- C. To detect, contain, and recover from security incidents
- D. To optimize routing protocols

Answer: C

Question: 5

A company wants to establish secure communication between its branch offices over the Internet. Which IPsec VPN mode is most appropriate for this site-to-site communication?

- A. SSL VPN
- B. GRE Tunnel
- C. Transport Mode
- D. IPsec Tunnel Mode

Answer: D

Question: 6

When configuring file filtering on a Huawei NGFW, which of the following parameters must be specified?

- A. DNS server
- B. File type
- C. IPsec proposal
- D. Certificate authority

Answer: B

Question: 7

What are common causes of SSL VPN access failures on Huawei NGFW?
(Choose two)

- A. Missing NAT policy
- B. Invalid user authentication
- C. Misconfigured certificate authority

D. Duplicate VPN IP pools

Answer: B,C

Question: 8

While troubleshooting an IPsec VPN, which log entries would indicate a Phase 2 negotiation failure?
(Choose two)

- A. INVALID_ID_INFORMATION
- B. NO_PROPOSAL_CHOSEN
- C. HASH_FAILED
- D. PROPOSAL_MISMATCH

Answer: B,D

Question: 9

Before enabling traffic flow between two VSYS instances, a _____ must be configured to facilitate inter-VSYS communication.

- A. NAT address pool
- B. Virtual link interface
- C. Physical loopback interface
- D. VLAN trunk

Answer: B

Question: 10

When configuring bandwidth management for web traffic, which of the following parameters is essential to define the maximum allowed bandwidth?

- A. DSCP tag
- B. Source interface
- C. CIR (Committed Information Rate)
- D. Logging interval

Answer: C

Thank You for Trying Our Product
Special 16 USD Discount Coupon: NSZUBG3X

Email: support@examsempire.com

**Check our Customer Testimonials and ratings
available on every product page.**

Visit our website.

<https://examsempire.com/>