

# Huawei

## H12-411\_V2.0

### HCIA-Data Center Facility V2.0

For More Information – Visit link below:

<https://www.examsempire.com/>

**Product Version**

1. Up to Date products, reliable and verified.
2. Questions and Answers in PDF Format.



<https://examsempire.com/>

Visit us at: <https://www.examsempire.com/h12-411-v2-0>

# Latest Version: 6.0

## Question: 1

Huawei monitoring system ECC800 The collector can be inserted at most \_\_\_\_\_ A power supply module.

**Answer: 2**

## Question: 2

In the dynamic environment monitoring system, \_\_\_\_\_ is used to indicate the severity of the corresponding fault.

**Answer: alarm level**

## Question: 3

ATS The dual power supply automatic switch can realize the fast mechanical switching of the two power supplies.

- A. True
- B. False

**Answer: A**

## Question: 4

In the access control system interface, the functions that can be realized are \_\_\_\_\_ .

**Answer: ABCD**

## Question: 5

The following are air-cooled row-level air conditioners \_\_\_\_\_ .

**Answer: Netcol5000-A**

**Thank You for Trying Our Product**

**Special 16 USD Discount Coupon: NSZUBG3X**

**Email:** [support@examsempire.com](mailto:support@examsempire.com)

**Check our Customer Testimonials and ratings  
available on every product page.**

**Visit our website.**

**<https://examsempire.com/>**