

# Latest Version: 11.0

## Question: 1

Application PDBs, SALES\_APP1 and SALES\_APP2, must be created and they must access common tables of the SALES\_APP application. Examine these steps:

Install the SALES\_APP application, including the common tables, in the application root.

Install the SALES\_APP application in the application root and the common tables in both the CDB root and the application root.

Create an application seed.

Install the SALES\_APP application in the application seed.

Create the SALES\_APP1 and SALES\_APP2 application PDBs.

Sync the SALES\_APP1 and SALES\_APP2 application PDBs with the application root.

Sync the SALES\_APP1 and SALES\_APP2 application PDBs with the application seed.

Sync the application seed with the application root. Which are the minimum required steps in the correct sequence?

- A. 1,3,5,7
- B. 2,5,6
- C. 1,5,6
- D. 3,4,1,6,8
- E. 1,3,5,6,7

**Answer: C**

## Question: 2

A container database, CDB1, contains a pluggable database PDB1. Another container database is called CDB2. You want to relocate PDB1 from CDB1 to CDB2 with near-zero down time. Which three are required?

- A. CDB2 must be in shared UNDO mode only.
- B. CDB2 must be in archivelog mode.
- C. CDB1 must be in archivelog mode.
- D. CDB1 and CDB2 must both be in local UNDO mode.
- E. CDB1 must be in shared UNDO mode only.
- F. CDB1 and CDB2 must be in shared UNDO mode.

**Answer: B, C, D**

### Question: 3

Which two are true about creating pluggable databases (PDBs) in Oracle 19c and later releases?

- A. A PDB snapshot depends on an existing storage snapshot of the source PDB.
- B. APDB snapshot can be a full copy of a source PDB.
- C. A PDB snapshot can be a sparse copy of a source PDB
- D. A snapshot copy PDB does not depend on an existing storage snapshot of the source PDB.
- E. A snapshot copy PDB can be a full copy of a source PDB

**Answer: B, C**

### Question: 4

Which two are true about creating RMAN backups for an Oracle container database?

- A. Online Redo Log backups can be created while connected to CDB\$ROOT
- B. Control file backups can be created while connected to CDB\$ROOT.
- C. The BACKUP TABLESPACE command can back up a pDB tablespace even if RMAN is connected to CDB\$ROOT.
- D. Archived Redo Log backups can be created while connected to PDB
- E. Control file backups cannot be created while connected to a PDB

**Answer: A, B**

### Question: 5

Which three are true about Automatic Workload Repository (AWR) snapshots?

- A. They can be retained forever.
- B. They are always created automatically.
- C. They are always created manually.
- D. They are generated if STATISTICS LEVEL is set to TYPICAL.
- E. They are generated if STATISTICS LEVEL is set to BASIC.
- F. They are generated if STATISTICS LEVEL is set to ALL.

**Answer: B, D, F**