CWNP

CWNA-110

CWNP Certified Wireless Network Administrator (CWNA)

For More Information – Visit link below:

https://www.examsempire.com/

Product Version

1. **Up to Date products, reliable and verified.**
2. **Questions and Answers in PDF Format.**



Latest Version: 6.0

Question: 1

During a post-implementation survey, you have detected a non-802.11 wireless device transmitting in the area used by handheld 802.11g scanners. What is the most important factor in determining the impact of this non-802.11 device?

A. Receive sensitivity
B. Channel occupied
C. Airtime utilization
D. Protocols utilized

Answer: C

Question: 2

What authentication method is referenced in the 802.11-2016 and 802.11-2020 specifications and is recommended for robust WLAN client security?

A. SSL
B. 802.1X/EAP
C. IPSec
D. WEP

Answer: B

Question: 3

What is required when operating 802.11ax APS in the 6 GHz band using passphrase-based authentication?

A. VHT PHY
B. HT PHY
C. SAE
D. CCMP

Answer: C

Question: 4

What is the most effective method for testing roaming in relation to 802.11 VoIP handsets?

A. Use a spectrum analyzer to monitor RF activity during a VoIP call.
B. Place a call with the handset and move around the facility to test quality during roaming.
C. Use a protocol analyzer to capture the traffic generated when a laptop roams.
D. Use the built-in roaming monitor built into all VoIP handsets.

Answer: B

Question: 5

What two ISM bands are used by microwave ovens, cordless home telephones, baby monitors, and wireless video cameras?
(Choose two)

A. 902 MHz
B. 2.4 GHz
C. 5.8 GHz
D. 7.6 GHz

Answer: B,C

Question: 6

_____ uses more bandwidth than is necessary to carry its data.

A. Narrowband
B. Frequency Hopping
C. Multipath Interference
D. Spread Spectrum

Answer: D

Question: 7

Which one of the following is not a factor considered when calculating the Link Budget for an outdoor point-to-point WLAN bridge link?

A. MU-MIMO capabilities of the bridges
B. Operating frequency
C. Receive antenna gain
D. Transmit power

Answer: A

Question: 8

You are performing a post-implementation validation survey. What basic tool can be used to easily locate areas of high co-channel interference?

A. Throughput tester
B. Laptop-based spectrum analyzer
C. Access point spectrum analyzer
D. Wi-Fi scanner

Answer: D

Question: 9

You are using a site survey tool for post-implementation validation. You have installed the appropriate adapter driver and imported a floor plan. Now, you want to take the next step in proper tool use.
What must you do before gathering survey data after the floor plan is imported?

A. Calibrate the floor plan
B. Install WinPCAP
C. Nothing, you can simply start capturing signal readings
D. Install iPerf

Answer: A

Question: 10

You have received a report of poor wireless connections on the third floor of a building under your administration. Three individuals have reported the problem. Apparently, the connections are reporting a strong signal, but the users cannot access the Internet.
With the problem identified, what is the next logical step in the troubleshooting process?

A. Verify the solution
B. Discover the scale of the problem
C. Perform corrective actions

D. Create a plan of action or escalate the problem

Answer: B

Thank You for Trying Our Product

Special 16 USD Discount Coupon: NSZUBG3X

Email: support@examsempire.com

Check our Customer Testimonials and ratings available on every product page.

Visit our website.

https://examsempire.com/